Shell Tellus S2 V 100

Version 1.2		Revision Date 2024.07.23	Print Date 2024.11.04
1. PRODUCT AND COMPANY ID	EN	TIFICATION	
Chemical product name	:	Shell Tellus S2 V 100	
Product code	:	001D7752	
Manufacturer or supplier's c Supplier's company name, address and phone number	deta		
Telephone Telefax	:	(+81) 03-3218-1780 (+81) 03-3218-1781	
Emergency telephone number	:	[Important notice for customer support If you need support for product, please service centre. Lub Customer Service Centre (Lub CS Tel. 0120-064-315 / Fax. 0120-264-31 E-mail. Inquiries-Lubes-JP@shell.com (Available for Japanese office hours or	contact our customer C) 5 (JP Toll free)
Contact for Safety Data Sheet	:	If you have any enquiries about the operation of the please email lubricantSDS@shell.com	
Recommended use of the ch	her	nical and restrictions on use	
Recommended use	:	Hydraulic oil	
Restrictions on use	:	This substance may not be used for an recommended without expert advice	ly purpose other than

2. HAZARDS IDENTIFICATION

GHS classification of chemical product

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements	
Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	: PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS:

Shell Tellus S2 V 100

Version 1.2	Revision Date 2024.07.23	Print Date 2024.11.04
	Not classified as a health hazard und	der GHS criteria.
	ENVIRONMENTAL HAZARDS:	
	Not classified as an environmental h	azard under GHS criteria.
-		
Precautionary statements		
	Prevention:	
	No precautionary phrases.	
	Response:	
	No precautionary phrases.	
	Storage:	
	No precautionary phrases.	
	Disposal:	
	No precautionary phrases.	

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.High-pressure injection under the skin may cause serious damage including local necrosis.Not classified as flammable but will burn.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).
	:	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9, 68649-12-7, 151006-60-9, 163149-28-8, 64741-88-4, 64741-89-5.

Hazardous components

Substance name	CAS-No.	Classification	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox.1; H304	0 - 90

2,6-di-tert-butyl	128-39-2	Skin Irrit.2; H315	0.1 - 0.24
phenol		Aquatic Acute1;	

Shell Tellus S2 V 100

Version 1.2	Revision Date 2024.07.23	Print Date 2024.11.04
	H400	
	Aquatic	
	Chronic1; H410	

For explanation of abbreviations see section 16.

4. FIRST-AID MEASURES	
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	 Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
	When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
In case of eye contact	 Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	: Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
	Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.
Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Notes to physician	: Treat symptomatically.
	High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt

Shell Tellus S2 V 100

Version 1.2	Revision Date 2024.07.23Print Date 2024.11.0surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.	4
5. FIRE-FIGHTING MEASURES		
Suitable extinguishing media	: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.	
Unsuitable extinguishing media	: Do not use water in a jet.	
Specific hazards during firefighting	 Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds. 	t
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Special protective equipment for firefighters	: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).	١

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to prevent uncontrolled release. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment

Shell Tellus S2 V 100

Version 1.2	Revision Date 2024.07.23 Print Date 2024.11.04
	see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.
7. HANDLING AND STORAGE	
Handling	
Technical measures	 Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	 Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Facial protective equipment	: If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
Describe contact avoidance, etc	: Strong oxidising agents.
Product Transfer	: Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Storage	
Other data	 Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
	Store at ambient temperature.
Packaging material	 Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	: Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Threshold limit value and permissible exposure limits for each component in the work environment

Components	CAS-No.	Value type (Form of	Control parameters /	Basis

Shell Tellus S2 V 100

Version 1.2	Revision Date 2024.07.23		Print Da	Print Date 2024.11.04	
		exposure)	Permissible		
			concentration		
Oil mist, mineral	Not Assigned			JP OEL	
	C C			JSOH	
	Further informa	ation: Group 1: c	arcinogenic to huma	าร	
Oil mist, mineral	Not Assigned	OEL-M (Mist)	3 mg/m3	JP OEL	
	_		-	JSOH	
	Further informa	ation: Substance	whose OEL is set ba	ased on non-	
	carcinogenic h	ealth effects. Se	e III, Group 1: carcine	ogenic to	
	humans			-	
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1	
Oil mist, mineral	Not Assigned	TWA	5 mg/m3	ACGIH	
		(Inhalable	0		
		particulate			
		matter)			

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

労働者の健康障害を防止するため化学物質の濃度基準値とその適用方法などを定めました (mhlw.go.jp)

Engineering measures :	 The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. 	
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated	
	General Information: Define procedures for safe handling and maintenance of controls.	

Shell Tellus S2 V 100

rsion 1.2	Revision Date 2024.07.23	Print Date 2024.11.04
	Educate and train workers in the measures relevant to normal act product. Ensure appropriate selection, tes equipment used to control expos equipment, local exhaust ventila Drain down system prior to equip maintenance. Retain drain downs in sealed sto subsequent recycle. Always observe good personal h washing hands after handling the drinking, and/or smoking. Routir protective equipment to remove contaminated clothing and footw Practice good housekeeping.	ivities associated with this sting and maintenance of sure, e.g. personal protective tion. oment break-in or orage pending disposal or nygiene measures, such as e material and before eating, nely wash work clothing and contaminants. Discard
Personal protective equip	oment	
Protective measures		
Personal protective equipn PPE suppliers.	nent (PPE) should meet recommended r	national standards. Check with
Respiratory protection	 No respiratory protection is ordin conditions of use. In accordance with good industri precautions should be taken to a If engineering controls do not ma concentrations to a level which is health, select respiratory protect specific conditions of use and ma Check with respiratory protective Where air-filtering respirators are appropriate combination of mask Select a filter suitable for the cor and vapours and particles [Type (149°F)]. 	al hygiene practices, avoid breathing of material. aintain airborne s adequate to protect worker ion equipment suitable for the eeting relevant legislation. e equipment suppliers. e suitable, select an c and filter. nbination of organic gases
Hand protection Remarks	: Where hand contact with the pro- gloves approved to relevant star US: F739) made from the followi suitable chemical protection. PV gloves Suitability and durability of usage, e.g. frequency and durati resistance of glove material, dex from glove suppliers. Contamina replaced. Personal hygiene is a care. Gloves must only be worn gloves, hands should be washed Application of a non-perfumed m	adards (e.g. Europe: EN374, ing materials may provide C, neoprene or nitrile rubber of a glove is dependent on on of contact, chemical terity. Always seek advice ted gloves should be key element of effective hand on clean hands. After using and dried thoroughly.

For continuous contact we recommend gloves with

Shell Tellus S2 V 100

Version 1.2	Revision Date 2024.07.23	Print Date 2024.11.04
	breakthrough time of more than 2 for > 480 minutes where suitable short-term/splash protection we re recognize that suitable gloves offer may not be available and in this of time maybe acceptable so long as and replacement regimes are follow a good predictor of glove resistan dependent on the exact composit Glove thickness should be typical depending on the glove make and	gloves can be identified. For ecommend the same but ering this level of protection ase a lower breakthrough s appropriate maintenance owed. Glove thickness is not ce to a chemical as it is ion of the glove material. ly greater than 0.35 mm
Eye and face protection	: If material is handled such that it of protective eyewear is recommend	
Skin and body protection	: Skin protection is not ordinarily re work clothes. It is good practice to wear chemic	
Thermal hazards	: Not applicable	
Environmental exposure c	ontrols	
General advice	: Take appropriate measures to full relevant environmental protection contamination of the environment Section 6. If necessary, prevent to being discharged to waste water. treated in a municipal or industria before discharge to surface water Local guidelines on emission limit must be observed for the discharg	legislation. Avoid by following advice given in undissolved material from Waste water should be I waste water treatment plant ts for volatile substances

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquid at room temperature.
Colour	: amber
Odour	: Data not available
Odour Threshold	: Data not available
рН	: Not applicable
pour point	: -30 °C / -22 °F Method: ISO 3016
Melting / freezing point	Data not available
Boiling point, initial boiling point and boiling range	: > 280 °C / 536 °Festimated value(s)
Flash point	: 225 °C / 437 °F

vapour.

Shell Tellus S2 V 100

sion 1.2	Revision Date 2024.07.23 Method: ISO 2592	Print Date 2024.11.04
Evaporation rate	: Data not available	
Flammability		
Flammability (solid, gas)	: Not applicable	
Flammability (liquids)	: Not classified as flammable but	will burn.
Lower explosion limit and upp	er explosion limit / flammability limit	
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	: >5	
Density and / or relative dens	ty	
Relative density	: 0.880 (15 °C / 59 °F)	
Density	: 880 kg/m3 (15.0 °C / 59.0 °F) Method: ISO 12185	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: log Pow: > 6 (based on information on simila	r products)
Auto-ignition point	: > 320 °C / 608 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity (Dynamic)	: Data not available	
Viscosity, kinematic	: 100 mm2/s (40.0 °C / 104.0 °F) Method: ASTM D445	
	14 mm2/s (100 °C / 212 °F) Method: ASTM D445	

Shell Tellus S2 V 100

Version 1.2	Revision Date 2024.07.23	Print Date 2024.11.04
Particle characteristics Particle size	: Data not available	
Explosive properties	: Classification Code: Not classified	
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected to be	a static accumulator.

10. STABILITY AND REACTIVITY	
Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Information on likely routes of exposure	:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity		
Product:		
Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity

Shell Tellus S2 V 100

Version 1.2	Revision Date 2024.07.23	Print Date 2024.11.04
	Based on available data, the classification	ation criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

Shell Tellus S2 V 100

Version 1.2 Revision Date 2024.07.23 Print Date 2024.11.04

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

12. ECOLOGICAL INFORMATION

Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Ecotoxicity	
Product:	
Toxicity to fish (Acute toxicity)	: Remarks: Based on available data, the classification criteria are not met. Practically non toxic: LL/EL/IL50 > 100 mg/I
Toxicity to crustacean (Acute	:

Shell Tellus S2 V 100

toxicity)		Revision Date 2024.07.23Print Date 2024.11.04Remarks: Based on available data, the classification criteria
		are not met. Practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to algae/aquatic plants (Acute toxicity)	:	Remarks: Based on available data, the classification criteria are not met. Practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to fish (Chronic toxicity)	:	Remarks: Based on available data, the classification criteria are not met.
Toxicity to crustacean (Chronic toxicity)	:	Remarks: Based on available data, the classification criteria are not met.
Toxicity to microorganisms (Acute toxicity)	:	Remarks: Based on available data, the classification criteria are not met.
<u>Components:</u> 2,6-di-tert-butyl phenol:		
M-Factor (Short-term (acute) aquatic hazard)	:	1
Persistence and degradability		
Product:		
Biodegradability	:	Remarks: Not readily biodegradable., Major constituents are inherently biodegradable, but contains components that may persist in the environment., Persistent per IMO criteria., International Oil Pollution Compensation (IOPC) Fund definition: "A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distils at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."
Bioaccumulation		
Product:		
Bioaccumulation	:	Remarks: Contains components with the potential to bioaccumulate.
Partition coefficient: n- octanol/water	:	log Pow: > 6Remarks: (based on information on similar products)
Mobility in soil		
Product:		
Mobility	:	Remarks: Liquid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be

Shell Tellus S2 V 100

Version 1.2		evision Date 2024.07.23 emarks: Floats on water.	Print Date 2024.11.04
Other adverse effects		smarks. Floats of water.	
no data available			
Product:			
Additional ecological information	oz is re co Po or Mi	bes not have ozone depletion per cone creation potential or global a mixture of non-volatile compo- leased to air in any significant q anditions of use. porly soluble mixture., Causes p ganisms. Ineral oil does not cause chronic ganisms at concentrations less	warming potential., Product onents, which will not be juantities under normal ohysical fouling of aquatic c toxicity to aquatic
Hazardous to the ozone layer			
Not applicable			
13. DISPOSAL CONSIDERATION	5		
Disposal methods			
Chemicals (residual waste)	It i to: de m W gr Do cc CC dr cc dr cc dr cc dr cc cc dr cc cc cc cc cc cc cc cc cc cc cc cc cc	ecover or recycle if possible. Is the responsibility of the waster xicity and physical properties of termine the proper waste class ethods in compliance with appli- aste product should not be allow ound water, or be disposed of in ponot dispose into the environme- ourses. To not dispose of tank water botto ain into the ground. This will res- intamination. aste arising from a spillage or ta- sposed of in accordance with pre- eferably to a recognised collect impetence of the collector or co- tablished beforehand.	the material generated to ification and disposal cable regulations. wed to contaminate soil or nto the environment. ent, in drains or in water oms by allowing them to sult in soil and groundwater ank cleaning should be revailing regulations, or or contractor. The
	Po	ARPOL - see International Com ollution from Ships (MARPOL 73 chnical aspects at controlling po	3/78) which provides
Contaminated containers and packaging	to th Di	spose in accordance with preva a recognized collector or contra e collector or contractor should sposal should be in accordance tional, and local laws and regul	actor. The competence of be established beforehand. with applicable regional,
Local legislation		sposal should be in accordance	

Shell Tellus S2 V 100

Version 1.2

Revision Date 2024.07.23 F national, and local laws and regulations.

Print Date 2024.11.04

14. TRANSPORT INFORMATION

Regulatory information when there are domestic regulations

Refer to section 15 for specific national regulation.

International Regulations

ADR

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

15. REGULATORY INFORMATION

Related Regulations

Fire Service Law

Group 4, Type 4 petroleums, (6000 litre), Hazardous rank III

Chemical Substance Control Law

Not applicable for Specified Chemical Substance, Monitoring Chemical Substance and Priority Assessment Chemical Substance.

Industrial Safety and Health Law

Harmful Substances Prohibited from Manufacture

Not applicable

Harmful Substances Required Permission for Manufacture

Not applicable

Substances Prevented From Impairment of Health

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 2: Information on Existing Chemicals having Mutagenicity

Not applicable

Shell Tellus S2 V 100

		having Mu	tagenicity	y - Annex 1: Information
igenici	nicity			
lames	es			
9)				
		Numbe	er	Concentration (%
		168		>=90 - <=100
Names	nes			
8)				
				Number
	-			168
s Due t	le to Sp	ecified Che	emical Su	Ibstances
Solve	lvent P	oisoning		
		•		
Safety	etv and	Health I av	w - Attach	ned table 1 (Dangerous
Ourcey	cty and			icu tubic i (Buligerous
CAS CO	S Contro	llaw		
	Contro			
_				
		of Specific to the Mana		I Substances in the
overne	ments		agement	THEIEOI
revent	ention e	etc Law		
-	-			
Enfor	oforcom	ent Order A	rt 3_1)	
			11. 5-4)	
g Law	aw			
report	orted in	n the follow	ving inver	ntories:
ompor	ponents	listed.		
	ponents	listed		
	nonente	listed		

16. OTHER INFORMATION

Full text of H-Statements

Shell Tellus S2 V 100

Version 1.2	Revision Date 2024.07.23	Print Date 2024.11.04
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
Full text of other ab	breviations	
Aquatic Acute	Short-term (acute) aquatic hazard	
Aquatic Chronic	Long-term (chronic) aquatic hazard	
Asp. Tox.	Aspiration hazard	

Skin Irrit. Skin irritation

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Further information

Training advice	: Provide adequate information, instruction and training for operators.	
Other information	: A vertical bar () in the left margin indicates an amendment from the previous version.	
Sources of key data used to compile the Safety Data	: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell	

Shell Tellus S2 V 100

Version 1.2Revision Date 2024.07.23Print Date 2024.11.04SheetHealth Services, material suppliers' data, CONCAWE, EU
IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

JP / EN