Shell Omala S2 G 100

Version 1.2 Revision Date 2024.07.15 Print Date 2024.11.04

1. PRODUCT AND COMPANY IDENTIFICATION

Chemical product name : Shell Omala S2 G 100

Product code : 001D7835

Manufacturer or supplier's details

Supplier's company name, : Shell Lubricants Japan K.K.

address and phone number Pacific Century Place Marunouchi 12F

1-11-1, Marunouchi

Chiyoda-ku Tokyo 100-6212

Japan

Telephone : (+81) 03-3218-1780 Telefax : (+81) 03-3218-1781

Emergency telephone : [Important notice for customer support]

number If you need support for product, please contact our customer

service centre.

Lub Customer Service Centre (Lub CSC)

Tel. 0120-064-315 / Fax. 0120-264-315 (JP Toll free)

E-mail. Inquiries-Lubes-JP@shell.com (Available for Japanese office hours only.)

Contact for Safety Data

Sheet

If you have any enquiries about the content of this SDS

please email lubricantSDS@shell.com

Recommended use of the chemical and restrictions on use

Recommended use : Gear lubricant.

Restrictions on use

This substance may not be used for any purpose other than

recommended without expert advice

2. HAZARDS IDENTIFICATION

GHS classification of chemical product

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:

Not classified as a health hazard under GHS criteria.

1 / 17 800001005752 JP

Shell Omala S2 G 100

Version 1.2 Revision Date 2024.07.15 Print Date 2024.11.04

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

Precautionary statements

Prevention:

No precautionary phrases.

Response:

No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Highly refined mineral oils and additives.

The highly refined mineral oil contains <3% (w/w) DMSO-

extract, according to IP346.

Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

* contains one or more of the following CAS-numbers: 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9, 68649-12-7, 151006-60-9, 163149-28-8, 64741-88-4,

64741-89-5.

Hazardous components

Contains no hazardous ingredients according to GHS

4. FIRST-AID MEASURES

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

Shell Omala S2 G 100

Version 1.2	Revision Date 2024.07.15	Print Date 2024.11.04
In case of skin contact	 : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. : Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continurinsing. If persistent irritation occurs, obtain medical attention. 	
In case of eye contact		
If swallowed	: In general no treatment is neces are swallowed, however, get me	
Most important symptoms and effects, both acute and delayed	 Oil acne/folliculitis signs and syn of black pustules and spots on the Ingestion may result in nausea, 	ne skin of exposed areas.
Protection of first-aiders	: When administering first aid, ens appropriate personal protective incident, injury and surroundings	equipment according to the
Notes to physician	: Treat symptomatically.	

5. FIRE-FIGHTING MEASURES

: Foam, water spray or fog. Dry chemical powder, carbon Suitable extinguishing media

dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing

media

: Do not use water in a jet.

Specific hazards during

firefighting

: Hazardous combustion products may include:

A complex mixture of airborne solid and liquid particulates and

gases (smoke).

Carbon monoxide may be evolved if incomplete combustion

occurs.

Unidentified organic and inorganic compounds.

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

6. ACCIDENTAL RELEASE MEASURES

Shell Omala S2 G 100

Version 1.2 Revision Date 2024.07.15 Print Date 2024.11.04

Personal precautions, protective equipment and emergency procedures Environmental precautions : Avoid contact with skin and eyes.

: Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate

barriers.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth

or other containment material.

Reclaim liquid directly or in an absorbent.

Soak up residue with an absorbent such as clay, sand or other

suitable material and dispose of properly.

Additional advice : For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

7. HANDLING AND STORAGE

Handling

Technical measures : Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Advice on safe handling : Avoid prolonged or repeated contact with skin.

Avoid inhaling vapour and/or mists.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning

materials in order to prevent fires.

Facial protective equipment : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Describe contact avoidance,

etc

: Strong oxidising agents.

Product Transfer : Proper grounding and bonding procedures should be used

during all bulk transfer operations to avoid static accumulation.

Storage

Other data : Keep container tightly closed and in a cool, well-ventilated

place.

4 / 17 800001005752 JP

Shell Omala S2 G 100

Version 1.2	Revision Date 2024.07.15	Print Date 2024.11.04	
	Use properly labeled and closable containers.		
	Store at ambient temperature.		
Packaging material	 Suitable material: For containers o steel or high density polyethylene. Unsuitable material: PVC. 	r container linings, use mild	
Container Advice	: Polyethylene containers should not temperatures because of possible		

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Threshold limit value and permissible exposure limits for each component in the work environment

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned			JP OEL JSOH
	Further information: Group 1: carcinogenic to humans			ns
Oil mist, mineral	Not Assigned	OEL-M (Mist)	3 mg/m3	JP OEL JSOH
	Further information: Substance whose OEL is set based on non-carcinogenic health effects. See III, Group 1: carcinogenic to humans			
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Shell Omala S2 G 100

Version 1.2 Revision Date 2024.07.15 Print Date 2024.11.04

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

労働者の健康障害を防止するため化学物質の濃度基準値とその適用方法などを定めました (mhlw.go.jp)

Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection

: No respiratory protection is ordinarily required under normal conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.

If engineering controls do not maintain airborne

concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an

appropriate combination of mask and filter.

Shell Omala S2 G 100

Version 1.2 Revision Date 2024.07.15 Print Date 2024.11.04

> Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Eye and face protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

: Skin protection is not ordinarily required beyond standard Skin and body protection

work clothes.

It is good practice to wear chemical resistant gloves.

Thermal hazards : Not applicable

Environmental exposure controls

: Take appropriate measures to fulfill the requirements of General advice

relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant

before discharge to surface water.

Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing

vapour.

Shell Omala S2 G 100

Version 1.2 Revision Date 2024.07.15 Print Date 2024.11.04

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquid at room temperature.

Colour : brown

Odour : Data not available
Odour Threshold : Data not available
pH : Not applicable
pour point : -24 °C / -11 °F

Method: ISO 3016

Melting / freezing point Data not available

Boiling point, initial boiling point and boiling range

: > 280 °C / 536 °Festimated value(s)

Flash point : 240 °C / 464 °F

Method: ISO 2592

Evaporation rate : Data not available

Flammability

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Not classified as flammable but will burn.

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : Typical 10 %(V)

Lower explosion limit : Typical 1 %(V)

Vapour pressure : < 0.5 Pa (20 °C / 68 °F)

estimated value(s)

Relative vapour density : > 5

Density and / or relative density

Relative density : 0.891 (15 °C / 59 °F)

Density : 891 kg/m3 (15.0 °C / 59.0 °F)

Method: ISO 12185

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : Data not available

8 / 17 800001005752 JP

Shell Omala S2 G 100

Version 1.2 Revision Date 2024.07.15 Print Date 2024.11.04

Partition coefficient: n-

: log Pow: > 6

octanol/water (based on information on similar products)

: > 320 °C / 608 °F Auto-ignition point

Decomposition temperature : Data not available

Viscosity

Viscosity (Dynamic) : Data not available

: 100 mm2/s (40.0 °C / 104.0 °F) Viscosity, kinematic

Method: ISO 3104

11.4 mm2/s (100 °C / 212 °F)

Method: ISO 3104

Particle characteristics

Particle size : Data not available

Explosive properties : Classification Code: Not classified

Oxidizing properties Data not available

Conductivity : This material is not expected to be a static accumulator.

10. STABILITY AND REACTIVITY

Reactivity : The product does not pose any further reactivity hazards in

addition to those listed in the following sub-paragraph.

Chemical stability : Stable.

Possibility of hazardous

reactions

: Reacts with strong oxidising agents.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Basis for assessment Information given is based on data on the components and

> the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a

9 / 17 800001005752 JΡ

Shell Omala S2 G 100

Version 1.2 Revision Date 2024.07.15 Print Date 2024.11.04

whole, rather than for individual component(s).

Information on likely routes of :

exposure

Skin and eye contact are the primary routes of exposure

although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 rat: > 5,000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the

classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Shell Omala S2 G 100

Version 1.2

Revision Date 2024.07.15

Print Date 2024.11.04

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data have not been determined specifically

for this product.

Shell Omala S2 G 100

Version 1.2 Revision Date 2024.07.15 Print Date 2024.11.04

Information given is based on a knowledge of the components

and the ecotoxicology of similar products.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for

individual component(s).

Ecotoxicity

Product:

Toxicity to fish (Acute

toxicity)

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic: LL/EL/IL50 > 100 mg/l

Toxicity to crustacean (Acute

toxicity)

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic: LL/EL/IL50 > 100 mg/l

Toxicity to algae/aquatic

plants (Acute toxicity)

Remarks: Based on available data, the classification criteria

are not met.

Practically non toxic: LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic

toxicity)

: Remarks: Based on available data, the classification criteria

are not met.

Toxicity to crustacean

(Chronic toxicity)

: Remarks: Based on available data, the classification criteria

are not met.

Toxicity to microorganisms

(Acute toxicity)

: Remarks: Based on available data, the classification criteria

are not met.

Persistence and degradability

Product:

Biodegradability : Remarks: Not readily biodegradable., Major constituents are inherently biodegradable, but contains components that may

persist in the environment., Persistent per IMO criteria., International Oil Pollution Compensation (IOPC) Fund definition: "A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distills at a

temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

Bioaccumulation

Product:

12 / 17 800001005752

JP

Shell Omala S2 G 100

Version 1.2 Revision Date 2024.07.15 Print Date 2024.11.04

Bioaccumulation : Remarks: Contains components with the potential to

bioaccumulate.

Partition coefficient: n-

octanol/water

: log Pow: > 6Remarks: (based on information on similar

products)

Mobility in soil

Product:

Mobility : Remarks: Liquid under most environmental conditions., If it

enters soil, it will adsorb to soil particles and will not be

mobile.

Remarks: Floats on water.

Other adverse effects

no data available

Product:

Additional ecological

information

: Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential., Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.

Poorly soluble mixture., Causes physical fouling of aquatic

organisms.

Mineral oil does not cause chronic toxicity to aquatic organisms at concentrations less than 1 mg/l.

Hazardous to the ozone layer

Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal methods

Chemicals (residual waste)

Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Waste product should not be allowed to contaminate soil or

ground water, or be disposed of into the environment.

Do not dispose into the environment, in drains or in water courses.

Jourses.

Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater

contamination.

Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be

established beforehand.

MARPOL - see International Convention for the Prevention of

Shell Omala S2 G 100

Version 1.2 Revision Date 2024.07.15 Print Date 2024.11.04 Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships. Contaminated containers and Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of packaging the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation

: Disposal should be in accordance with applicable regional, Remarks

national, and local laws and regulations.

14. TRANSPORT INFORMATION

Regulatory information when there are domestic regulations

Refer to section 15 for specific national regulation.

International Regulations

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

15. REGULATORY INFORMATION

Related Regulations

Fire Service Law

Group 4, Type 4 petroleums, (6000 litre), Hazardous rank III

Chemical Substance Control Law

Priority Assessment Chemical Substance

Chemical name	Number
Alkan-1-amine(C=8,10,12,14,16,18, normal chain), (Z)-Octadec-9-en-1-	164

Shell Omala S2 G 100

Version 1.2Revision Date 2024.07.15Print Date 2024.11.04amine or (9Z,12Z)-Octadeca-9,12-dien-1-amine

Industrial Safety and Health Law

Harmful Substances Prohibited from Manufacture

Not applicable

Harmful Substances Required Permission for Manufacture

Not applicable

Substances Prevented From Impairment of Health

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 2: Information on Existing Chemicals having Mutagenicity

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 1: Information on Notified Substances having Mutagenicity

Not applicable

Substances Subject to be Notified Names

Article 57-2 (Enforcement Order Table 9)

Chemical name	Number	Concentration (%)
Mineral oil	168	>=90 - <=100

Substances Subject to be Indicated Names

Article 57 (Enforcement Order Article 18)

Chemical name	Number
Mineral oil	168

Ordinance on Prevention of Hazards Due to Specified Chemical Substances

Not applicable

Ordinance on Prevention of Organic Solvent Poisoning

Not applicable

Enforcement Order of the Industrial Safety and Health Law - Attached table 1 (Dangerous Substances)

Not applicable

Poisonous and Deleterious Substances Control Law

Not applicable

Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof

Not applicable

Vessel Safety Law

Not applicable

Aviation Law

Not applicable

Marine Pollution and Sea Disaster Prevention etc Law

Not classified as marine pollutant

Shell Omala S2 G 100

Version 1.2 Revision Date 2024.07.15 Print Date 2024.11.04

Water Pollution Control Law

Oil emissions regulations (Law Art. 2-5, Enforcement Order Art. 3-4)

Waste Disposal and Public Cleansing Law

Industrial waste

The components of this product are reported in the following inventories:

TSCA : All components listed.

ENCS : All components listed.

16. OTHER INFORMATION

Abbreviations and Acronyms

AllC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System: GLP - Good Laboratory Practice: IARC - International Agency for Research on Cancer: IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Further information

Training advice : Provide adequate information, instruction and training for

operators.

Shell Omala S2 G 100

Version 1.2	Revision Date 2024.07.15	Print Date 2024.11.04	
Other information	: A vertical bar () in the left margin if from the previous version.	ndicates an amendment	
Sources of key data used to compile the Safety Data Sheet	: The quoted data are from, but not sources of information (e.g. toxicol Health Services, material suppliers IUCLID date base, EC 1272 regula	logical data from Shell 3' data, CONCAWE, EU	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

JP / EN