Shell Omala S2 G 220

Version 1.1		Revision Date 2024.07.15	Print Date 2024.11.04
1. PRODUCT AND COMPANY IDE	ΞΝ٦	TIFICATION	
Chemical product name	:	Shell Omala S2 G 220	
Product code	:	001D7837	
Manufacturer or supplier's d Supplier's company name, address and phone number	leta :	Shell Lubricants Japan K.K. Pacific Century Place Marunouchi 12F 1-11-1, Marunouchi Chiyoda-ku Tokyo 100-6212	
Telephone Telefax	:	Japan (+81) 03-3218-1780 (+81) 03-3218-1781	
Emergency telephone number	:	[Important notice for customer support] If you need support for product, please service centre. Lub Customer Service Centre (Lub CSC Tel. 0120-064-315 / Fax. 0120-264-315 E-mail. Inquiries-Lubes-JP@shell.com (Available for Japanese office hours on	contact our customer C) 5 (JP Toll free)
Contact for Safety Data Sheet	:	If you have any enquiries about the coperation please email lubricantSDS@shell.com	
Recommended use of the ch	nen	nical and restrictions on use	
Recommended use	:	Gear lubricant.	
Restrictions on use	:	This substance may not be used for any recommended without expert advice	y purpose other than

2. HAZARDS IDENTIFICATION

GHS classification of chemical product Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements	
Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria.

Shell Omala S2 G 220

Version 1.1	Revision Date 2024.07.15	Print Date 2024.11.04
	ENVIRONMENTAL HAZARDS:	
	Not classified as an environmental	hazard under GHS criteria.
-		
Precautionary statements		
	Prevention:	
	No precautionary phrases.	
	Response:	
	No precautionary phrases.	
	Storage:	
	No precautionary phrases.	
	Disposal:	
	No precautionary phrases.	

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	: Mixture
Chemical nature	 Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).
	 * contains one or more of the following CAS-numbers: 64742 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69 9, 68649-12-7, 151006-60-9, 163149-28-8, 64741-88-4, 64741-89-5.

Hazardous components

Contains no hazardous ingredients according to GHS

4. FIRST-AID MEASURES

If inhaled

: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.

Shell Omala S2 G 220

Version 1.1	Revision Date 2024.07.15	Print Date 2024.11.04
In case of skin contact	: Remove contaminated clothing. water and follow by washing with If persistent irritation occurs, obta	n soap if available.
In case of eye contact	 Flush eye with copious quantities Remove contact lenses, if preser rinsing. If persistent irritation occurs, obtain 	nt and easy to do. Continue
If swallowed	: In general no treatment is necess are swallowed, however, get me	
Most important symptoms and effects, both acute and delayed	: Oil acne/folliculitis signs and sym of black pustules and spots on th Ingestion may result in nausea, w	ne skin of exposed areas.
Protection of first-aiders	: When administering first aid, ens appropriate personal protective e incident, injury and surroundings.	equipment according to the
Notes to physician	: Treat symptomatically.	

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during firefighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

6. ACCIDENTAL RELEASE MEASURES

Shell Omala S2 G 220

Version 1.1	Revision Date 2024.07.15	Print Date 2024.11.04
Personal precautions, protective equipment and emergency procedures	: Avoid contact with skin and eyes.	
Environmental precautions	 Use appropriate containment to avo contamination. Prevent from spread ditches or rivers by using sand, ear barriers. Local authorities should be advised cannot be contained. 	ding or entering drains, th, or other appropriate
Methods and materials for containment and cleaning up	: Slippery when spilt. Avoid accident Prevent from spreading by making or other containment material. Reclaim liquid directly or in an absor Soak up residue with an absorbent suitable material and dispose of pro-	a barrier with sand, earth orbent. such as clay, sand or other
Additional advice	: For guidance on selection of persor see Section 8 of this Safety Data S For guidance on disposal of spilled this Safety Data Sheet.	heet.

Handling	
Technical measures	: Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposa this material.
Advice on safe handling	: Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Facial protective equipment	: If material is handled such that it could be splashed into eye protective eyewear is recommended.
Describe contact avoidance, etc	: Strong oxidising agents.
Product Transfer	: Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulati
Storage	
Other data	: Keep container tightly closed and in a cool, well-ventilated place.

Version 1.1	Revision Date 2024.07.15	Print Date 2024.11.04
	Use properly labeled and closable	containers.
	Store at ambient temperature.	
Packaging material	: Suitable material: For containers of steel or high density polyethylene. Unsuitable material: PVC.	
Container Advice	: Polyethylene containers should no temperatures because of possible	

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Threshold limit value and permissible exposure limits for each component in the work environment

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned			JP OEL JSOH
	Further informa	ation: Group 1: c	arcinogenic to humar	าร
Oil mist, mineral	Not Assigned	OEL-M (Mist)	3 mg/m3	JP OEL JSOH
			e whose OEL is set ba e III, Group 1: carcino	
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Biological occupational exposure limits

Biological Limit Values (BLV) have not been established for this material.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany

Shell Omala S2 G 220

Version 1.1	Revision Date 2024.07.15	Print Date 2024.11.04
http://www.dguv.de/inhalt/index.js L'Institut National de Recherche	p et de Securité, (INRS), France http://www	<i>.</i> .inrs.fr/accueil
労働者の健康障害を防止するた (mhlw.go.jp)	め化学物質の濃度基準値とその適用方法は	などを定めました
Engineering measures	The level of protection and types of convary depending upon potential exposure controls based on a risk assessment of Appropriate measures include: Adequate ventilation to control airborne Where material is heated, sprayed or m	e conditions. Select local circumstances. concentrations.
	greater potential for airborne concentrat General Information: Define procedures for safe handling and controls. Educate and train workers in the hazard measures relevant to normal activities a product. Ensure appropriate selection, testing ar equipment used to control exposure, e. equipment, local exhaust ventilation. Drain down system prior to equipment I maintenance. Retain drain downs in sealed storage p subsequent recycle. Always observe good personal hygiene washing hands after handling the mater drinking, and/or smoking. Routinely wa protective equipment to remove contam contaminated clothing and footwear that Practice good housekeeping.	d maintenance of ds and control associated with this nd maintenance of g. personal protective break-in or brending disposal or e measures, such as rial and before eating, ash work clothing and ninants. Discard

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection	 No respiratory protection is ordinarily required under normal conditions of use.
	In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases

Version 1.1	Revision Date 2024.07.15 Print Date 2024.11.04
	and vapours and particles [Type A/Type P boiling point >65°C (149°F)].
Hand protection Remarks	: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
	For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.
Eye and face protection	: If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
Skin and body protection	 Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.
Thermal hazards	: Not applicable
Environmental exposure co	ontrols
General advice	: Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from

treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

being discharged to waste water. Waste water should be

ion 1.1	Revision Date 2024.07.15	Print Date 2024.11.
HYSICAL AND CHEMICAL P	ROPERTIES	
Physical state	: Liquid at room temperature.	
Colour	: brown	
Odour	: Data not available	
Odour Threshold	: Data not available	
рН	: Not applicable	
pour point	: -18 °C / -0.40 °F Method: ISO 3016	
Melting / freezing point	Data not available	
Boiling point, initial boiling point and boiling range	: > 280 °C / 536 °Festimated value(s)	
Flash point	: 240 °C / 464 °F Method: ISO 2592	
Evaporation rate	: Data not available	
Flammability		
Flammability (solid, gas)	: Not applicable	
Flammability (liquids)	: Not classified as flammable but will h	burn.
Lower explosion limit and upp	er explosion limit / flammability limit	
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	: >5	
Density and / or relative density	ity	
Relative density	: 0.899 (15 °C / 59 °F)	
Density	: 899 kg/m3 (15.0 °C / 59.0 °F) Method: ISO 12185	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	

Shell Omala S2 G 220

Version 1.1	Revision Date 2024.07.15 Print Date 2024.	.11.04
Partition coefficient: n- octanol/water	: log Pow: > 6 (based on information on similar products)	
Auto-ignition point	: > 320 °C / 608 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity (Dynamic)	: Data not available	
Viscosity, kinematic	: 220 mm2/s (40.0 °C / 104.0 °F) Method: ISO 3104	
	19.4 mm2/s (100 °C / 212 °F) Method: ISO 3104	
Particle characteristics Particle size	: Data not available	
Explosive properties	: Classification Code: Not classified	
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected to be a static accumulator.	
10. STABILITY AND REACTIVITY		
Reactivity	: The product does not pose any further reactivity hazards i addition to those listed in the following sub-paragraph.	in
Chemical stability	: Stable.	

Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a

-

Shell Omala S2 G 220

Version 1.1		Revision Date 2024.07.15 whole, rather than for individual compone	Print Date 2024.11.04 ent(s).
Information on likely routes of exposure	:	Skin and eye contact are the primary rou although exposure may occur following a	•
Acute toxicity			
Product:			
Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification	on criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the care not met.	lassification criteria
Acute dermal toxicity	:	LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification	on criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

 Version 1.1
 Revision
 Date 2024.07.15
 Print Date 2024.11.04

 Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).
 Print Date 2024.11.04

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

:

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data have not been determined specifically for this product.

Version 1.1	Revision Date 2024.07.15	Print Date 2024.11.04
	Information given is based on a known and the ecotoxicology of similar pro Unless indicated otherwise, the data representative of the product as a windividual component(s).	ducts. a presented is
Ecotoxicity		
Product:		
Toxicity to fish (Acute toxicity)	: Remarks: Based on available data, are not met. Practically non toxic: LL/EL/IL50 > 100 mg/I	the classification criteria
Toxicity to crustacean (Acute toxicity)	: Remarks: Based on available data, are not met. Practically non toxic: LL/EL/IL50 > 100 mg/I	the classification criteria
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: Based on available data, are not met. Practically non toxic: LL/EL/IL50 > 100 mg/I	the classification criteria
Toxicity to fish (Chronic toxicity)	: Remarks: Based on available data, are not met.	the classification criteria
Toxicity to crustacean (Chronic toxicity)	: Remarks: Based on available data, are not met.	the classification criteria
Toxicity to microorganisms (Acute toxicity)	: Remarks: Based on available data, are not met.	the classification criteria
Persistence and degradability		
Product:		
Biodegradability	: Remarks: Not readily biodegradable inherently biodegradable, but conta persist in the environment., Persiste International Oil Pollution Compense definition: "A non-persistent oil is oil shipment, consists of hydrocarbon f of which, by volume, distills at a ten and (b) at least 95% of which, by vo temperature of 370°C (700°F) when Method D-86/78 or any subsequent	ins components that may ent per IMO criteria., ation (IOPC) Fund , which, at the time of fractions, (a) at least 50% nperature of 340°C (645°F) lume, distils at a tested by the ASTM

Bioaccumulation

Product:

Version 1.1	Revision Date 2024.07	07.15 Print Date 2024.11.04
Bioaccumulation	: Remarks: Contains cor bioaccumulate.	omponents with the potential to
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: products)	: (based on information on similar
Mobility in soil		
Product:		
Mobility		er most environmental conditions., If it orborb to soil particles and will not be vater.
Other adverse effects		
no data available <u>Product:</u>		
Additional ecological information	ozone creation potentia is a mixture of non-vola released to air in any s conditions of use. Poorly soluble mixture. organisms. Mineral oil does not cau	depletion potential, photochemical ial or global warming potential., Product atile components, which will not be significant quantities under normal e., Causes physical fouling of aquatic ause chronic toxicity to aquatic rations less than 1 mg/l.

Hazardous to the ozone layer

Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal methods

Chemicals (residual waste)	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
	MARROL and International Computing for the Broughting of

MARPOL - see International Convention for the Prevention of

Version 1.1	Revision Date 2024.07.15	Print Date 2024.11.04
	Pollution from Ships (MARPOL 73/78) we technical aspects at controlling pollution	•
Contaminated containers and packaging	: Dispose in accordance with prevailing r to a recognized collector or contractor. the collector or contractor should be est Disposal should be in accordance with national, and local laws and regulations	The competence of tablished beforehand. applicable regional,
Local legislation Remarks	: Disposal should be in accordance with a national, and local laws and regulations	

14. TRANSPORT INFORMATION

Regulatory information when there are domestic regulations

Refer to section 15 for specific national regulation.

International Regulations

ADR

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

15. REGULATORY INFORMATION

Related Regulations

Fire Service Law

Group 4, Type 4 petroleums, (6000 litre), Hazardous rank III

Chemical Substance Control Law

Priority Assessment Chemical Substance

(Chemical name	Number
/	Alkan-1-amine(C=8,10,12,14,16,18, normal chain), (Z)-Octadec-9-en-1-	164

Shell Omala S2 G 220

rsion 1.1	Revision Date 2024.07.15	Print Date 2024.11.04
	adeca-9,12-dien-1-amine	
Industrial Safety and	Health Law	
Harmful Substances	Prohibited from Manufacture	
Harmful Substances	Required Permission for Manufacture	
Substances Prevente Not applicable	d From Impairment of Health	
	nformation on Chemicals having Mutag s having Mutagenicity	genicity - Annex 2: Information
	nformation on Chemicals having Mutages having Mutages having Mutagenicity	genicity - Annex 1: Information
Substances Subject t Article 57-2 (Enforceme		
Chemical name	Number	Concentration (%)
Mineral oil	168	>=90 - <=100
Chemical name Mineral oil		Number 168
Ordinance on Preven Not applicable	tion of Hazards Due to Specified Chem	nical Substances
	tion of Organic Solvent Poisoning	
	f the Industrial Safety and Health Law	- Attached table 1 (Dangerous
Not applicable		
Poisonous and Delete Not applicable	erious Substances Control Law	
	etc. of Release Amounts of Specific Cl motion of Improvements to the Manag	
Vessel Safety Law		
Not applicable		
Aviation Law		
Not applicable		
Marine Pollution and	Sea Disaster Prevention etc Law	
Not classified as marine	e pollutant	

Version 1.1	Revision Date 2024.07.15	Print Date 2024.11.04		
Water Pollution Control	Law			
Oil emissions regulations	(Law Art. 2-5, Enforcement Order Art. 3-4)			
Waste Disposal and Pu Industrial waste	blic Cleansing Law			
The components of this product are reported in the following inventories:				
TSCA	: All components listed.			
ENCS	: All components listed.			

16. OTHER INFORMATION

Abbreviations and Acronyms

AllC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System: GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitorv concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Further information

Training advice

: Provide adequate information, instruction and training for operators.

Shell Omala S2 G 220

Version 1.1	Revision Date 2024.07.15	Print Date 2024.11.04
Other information	: A vertical bar () in the left margin in from the previous version.	ndicates an amendment
Sources of key data used to compile the Safety Data Sheet	: The quoted data are from, but not l sources of information (e.g. toxicole Health Services, material suppliers IUCLID date base, EC 1272 regula	ogical data from Shell ' data, CONCAWE, EU

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

JP / EN