Shell Omala S2 G 460

Version 1.1		Revision Date 2024.07.03	Print Date 2024.11.04
1. PRODUCT AND COMPANY IDE	ENT	TIFICATION	
Chemical product name	:	Shell Omala S2 G 460	
Product code	:	001D7839	
Manufacturer or supplier's d Supplier's company name, address and phone number	leta :		
Telephone Telefax		(+81) 03-3218-1780 (+81) 03-3218-1781	
Emergency telephone number	:	[Important notice for customer support] If you need support for product, please service centre. Lub Customer Service Centre (Lub CSC Tel. 0120-064-315 / Fax. 0120-264-315 E-mail. Inquiries-Lubes-JP@shell.com (Available for Japanese office hours on	contact our customer C) 5 (JP Toll free)
Contact for Safety Data Sheet	:	If you have any enquiries about the coperation please email lubricantSDS@shell.com	
Recommended use of the ch	nen	nical and restrictions on use	
Recommended use	:	Gear lubricant.	
Restrictions on use	:	This substance may not be used for any recommended without expert advice	y purpose other than

2. HAZARDS IDENTIFICATION

GHS classification of chemical product Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements	
Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria.

Shell Omala S2 G 460

Version 1.1	Revision Date 2024.07.03	Print Date 2024.11.04
	ENVIRONMENTAL HAZARDS:	
	Not classified as an environmental	hazard under GHS criteria.
Precautionary statements	:	
	Prevention:	
	No precautionary phrases.	
	Response:	
	No precautionary phrases.	
	Storage:	
	No precautionary phrases.	
	Disposal:	
	No precautionary phrases.	

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).
	:	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9, 68649-12-7, 151006-60-9, 163149-28-8, 64741-88-4, 64741-89-5.

Hazardous components

Contains no hazardous ingredients according to GHS

4. FIRST-AID MEASURES

If inhaled

: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.

Shell Omala S2 G 460

Version 1.1	Revision Date 2024.07.03	Print Date 2024.11.04
In case of skin contact	: Remove contaminated clothing. water and follow by washing with If persistent irritation occurs, obta	n soap if available.
In case of eye contact	 Flush eye with copious quantities Remove contact lenses, if preser rinsing. If persistent irritation occurs, obtained 	nt and easy to do. Continue
If swallowed	: In general no treatment is neces are swallowed, however, get me	,
Most important symptoms and effects, both acute and delayed	: Oil acne/folliculitis signs and syn of black pustules and spots on th Ingestion may result in nausea, y	he skin of exposed areas.
Protection of first-aiders	: When administering first aid, ens appropriate personal protective e incident, injury and surroundings.	equipment according to the
Notes to physician	: Treat symptomatically.	

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during firefighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

6. ACCIDENTAL RELEASE MEASURES

Shell Omala S2 G 460

Version 1.1	Revision Date 2024.07.03	Print Date 2024.11.04
Personal precautions, protective equipment and emergency procedures	: Avoid contact with skin and	eyes.
Environmental precautions	ditches or rivers by using sa barriers.	t to avoid environmental spreading or entering drains, nd, earth, or other appropriate advised if significant spillages
Methods and materials for containment and cleaning up	 Slippery when spilt. Avoid a Prevent from spreading by n or other containment materia Reclaim liquid directly or in a 	an absorbent. corbent such as clay, sand or other
Additional advice	see Section 8 of this Safety	f personal protective equipment Data Sheet. spilled material see Section 13 of

Handling	
Technical measures	: Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and dispos this material.
Advice on safe handling	 Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Facial protective equipment	: If material is handled such that it could be splashed into ey protective eyewear is recommended.
Describe contact avoidance, etc	: Strong oxidising agents.
Product Transfer	: Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumula
Storage	
Other data	: Keep container tightly closed and in a cool, well-ventilated place.

Version 1.1	Revision Date 2024.07.03	Print Date 2024.11.04
	Use properly labeled and closable	containers.
	Store at ambient temperature.	
Packaging material	: Suitable material: For containers of steel or high density polyethylene. Unsuitable material: PVC.	or container linings, use mild
Container Advice	: Polyethylene containers should no temperatures because of possible	

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Threshold limit value and permissible exposure limits for each component in the work environment

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned			JP OEL JSOH
	Further informa	ation: Group 1: c	arcinogenic to humar	าร
Oil mist, mineral	Not Assigned	OEL-M (Mist)	3 mg/m3	JP OEL JSOH
			e whose OEL is set ba e III, Group 1: carcino	
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

http://www.dguv.de/inhalt/ind	
	rche et de Securité, (INRS), France http://www.inrs.fr/accueil るため化学物質の濃度基準値とその適用方法などを定めました
(mnw.go.jp) Engineering measures	 The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and
	protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection	 No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

sion 1.1	Revision Date 2024.07.03 Print Date 2024.1 Select a filter suitable for the combination of organic gases
	and vapours and particles [Type A/Type P boiling point >65 (149°F)].
Hand protection	
Remarks	: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN37- US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubbo gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective ha care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended
	For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. I short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.
Eye and face protection	: If material is handled such that it could be splashed into ey protective eyewear is recommended.
Skin and body protection	 Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.
	it is your plactice to wear chemical resistant gives.

Environmental exposure controls

General advice	 Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.
	vapour.

sion 1.1	Revision Date 2024.07.03	Print Date 2024.11
HYSICAL AND CHEMICAL P	ROPERTIES	
Physical state	: Liquid at room temperature.	
Colour	: brown	
Odour	: Data not available	
Odour Threshold	: Data not available	
рН	: Not applicable	
pour point	: -12 °C / 10 °F Method: ISO 3016	
Melting / freezing point	Data not available	
Boiling point, initial boiling point and boiling range	: > 280 °C / 536 °Festimated value(s)	
Flash point	: 260 °C / 500 °F Method: ISO 2592	
Evaporation rate	: Data not available	
Flammability		
Flammability (solid, gas)	: Not applicable	
Flammability (liquids)	: Not classified as flammable but will	burn.
Lower explosion limit and upp	per explosion limit / flammability limit	
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	: >5	
Density and / or relative density	ity	
Relative density	: 0.904 (15 °C / 59 °F)	
Density	: 904 kg/m3 (15.0 °C / 59.0 °F) Method: ISO 12185	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	

Shell Omala S2 G 460

Version 1.1	Revision Date 2024.07.03	Print Date 2024.11.04
Partition coefficient: n-	: log Pow: > 6	
octanol/water	(based on information on similar produc	sts)
Auto-ignition point	: > 320 °C / 608 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity (Dynamic)	: Data not available	
Viscosity, kinematic	: 460 mm2/s (40.0 °C / 104.0 °F) Method: ISO 3104	
	30.8 mm2/s (100 °C / 212 °F) Method: ISO 3104	
Particle characteristics Particle size	: Data not available	
Explosive properties	: Classification Code: Not classified	
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected to be a st	atic accumulator.
10. STABILITY AND REACTIVITY		
Reactivity	: The product does not pose any further addition to those listed in the following	

11.	TOXICOL	OGICAL	INFORMATION

Chemical stability

Conditions to avoid

reactions

products

Possibility of hazardous

Incompatible materials

Hazardous decomposition

Basis for assessment : Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise the data presented is representative of the product as a	
--	--

: Strong oxidising agents.

: Reacts with strong oxidising agents.

: Extremes of temperature and direct sunlight.

: No decomposition if stored and applied as directed.

: Stable.

-

Shell Omala S2 G 460

Version 1.1		Revision Date 2024.07.03Print Date 2024.11.04whole, rather than for individual component(s).	
Information on likely routes of exposure	:	Skin and eye contact are the primary rou although exposure may occur following a	•
Acute toxicity			
Product:			
Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification	on criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the care not met.	classification criteria
Acute dermal toxicity	:	LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification	on criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

 Version 1.1
 Revision
 Date 2024.07.03
 Print Date 2024.11.04

 Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).
 Print Date 2024.11.04

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

:

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data have not been determined specifically for this product.

Version 1.1	Revision Date 2024.07.03 Print Da	ate 2024.11.04
	Information given is based on a knowledge of the and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather the individual component(s).	;
Ecotoxicity		
Product:		
Toxicity to fish (Acute toxicity)	: Remarks: Based on available data, the classificat are not met. Practically non toxic: LL/EL/IL50 > 100 mg/l	ion criteria
Toxicity to crustacean (Acute toxicity)	: Remarks: Based on available data, the classificat are not met. Practically non toxic: LL/EL/IL50 > 100 mg/l	ion criteria
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: Based on available data, the classificat are not met. Practically non toxic: LL/EL/IL50 > 100 mg/l	ion criteria
Toxicity to fish (Chronic toxicity)	: Remarks: Based on available data, the classificat are not met.	ion criteria
Toxicity to crustacean (Chronic toxicity)	: Remarks: Based on available data, the classificat are not met.	ion criteria
Toxicity to microorganisms (Acute toxicity)	: Remarks: Based on available data, the classificat are not met.	ion criteria
Persistence and degradability		
Product:		
Biodegradability	: Remarks: Not readily biodegradable., Major cons inherently biodegradable, but contains componen persist in the environment., Persistent per IMO cr International Oil Pollution Compensation (IOPC) definition: "A non-persistent oil is oil, which, at the shipment, consists of hydrocarbon fractions, (a) a of which, by volume, distills at a temperature of 3 and (b) at least 95% of which, by volume, distils a temperature of 370°C (700°F) when tested by the Method D-86/78 or any subsequent revision there	ts that may riteria., Fund e time of at least 50% 40°C (645°F) at a e ASTM

Bioaccumulation

Product:

Version 1.1	Revision Date 2024	1.07.03 Prir	nt Date 2024.11.04
Bioaccumulation	: Remarks: Contains of bioaccumulate.	Remarks: Contains components with the potential to bioaccumulate.	
Partition coefficient: n- octanol/water	: log Pow: > 6Remark products)	log Pow: > 6Remarks: (based on information on similar products)	
Mobility in soil			
Product:			
Mobility		der most environmental of sorb to soil particles and water.	
Other adverse effects			
no data available <u>Product:</u>			
Additional ecological information	ozone creation poter is a mixture of non-w released to air in any conditions of use. Poorly soluble mixtu organisms. Mineral oil does not	ne depletion potential, pho ntial or global warming p volatile components, which y significant quantities ur ure., Causes physical foul cause chronic toxicity to ntrations less than 1 mg/	otential., Product ch will not be nder normal ling of aquatic aquatic

Hazardous to the ozone layer

Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal methods

Chemicals (residual waste)	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
	MARROL and International Convention for the Provention of

MARPOL - see International Convention for the Prevention of

Version 1.1	Revision Date 2024.07.03	Print Date 2024.11.04
	Pollution from Ships (MARPOL 73/78) we technical aspects at controlling pollution	•
Contaminated containers and packaging	Dispose in accordance with prevailing re- to a recognized collector or contractor. the collector or contractor should be est Disposal should be in accordance with national, and local laws and regulations	The competence of tablished beforehand. applicable regional,
Local legislation Remarks	: Disposal should be in accordance with a national, and local laws and regulations	

14. TRANSPORT INFORMATION

Regulatory information when there are domestic regulations

Refer to section 15 for specific national regulation.

International Regulations

ADR

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

15. REGULATORY INFORMATION

Related Regulations

Fire Service Law

Group 4, Type 4 petroleums, (6000 litre), Hazardous rank III

Chemical Substance Control Law

Priority Assessment Chemical Substance

Chemical name	Number
Alkan-1-amine(C=8,10,12,14,16,18, normal chain), (Z)-Octadec-9-en-1-	164

Shell Omala S2 G 460

Version 1.1	Revision Date 2024.07.03	Print Date 2024.11.04		
amine or (9Z,12Z)-Oct	adeca-9,12-dien-1-amine			
Priority Assessment Chemical Substance				
Chemical name		Number		
Ethyl acrylate		32		
Industrial Safety and Health Law				
Harmful Substances Prohibited from Manufacture				

Not applicable

Harmful Substances Required Permission for Manufacture

Not applicable

Substances Prevented From Impairment of Health

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 2: Information on Existing Chemicals having Mutagenicity

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 1: Information on Notified Substances having Mutagenicity

Not applicable

Substances Subject to be Notified Names

Article 57-2 (Enforcement Order Table 9)			
Chemical name	Number	Concentration (%)	
Mineral oil	168	>=90 - <=100	

Substances Subject to be Indicated Names

Article 57 (Enforcement Order Article 18)

Chemical name	Number
Mineral oil	168

Ordinance on Prevention of Hazards Due to Specified Chemical Substances

Not applicable

Ordinance on Prevention of Organic Solvent Poisoning

Not applicable

Enforcement Order of the Industrial Safety and Health Law - Attached table 1 (Dangerous Substances)

Not applicable

Poisonous and Deleterious Substances Control Law

Not applicable

Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof Not applicable

Vessel Safety Law

Not applicable

Aviation Law

Not applicable

Version 1.1	Revision Date 2024.07.03	Print Date 2024.11.04		
Marine Pollution and Sea Disaster Prevention etc Law				
Not classified as marine po	Not classified as marine pollutant			
Water Pollution Control Law				
Oil emissions regulations (Law Art. 2-5, Enforcement Order Art. 3-4)				
Waste Disposal and Public Cleansing Law Industrial waste				
The components of this p	ventories:			
TSCA	: All components listed.			
ENCS	: All components listed.			

16. OTHER INFORMATION

Abbreviations and Acronyms

AllC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZloC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship: REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Further information

Training advice

: Provide adequate information, instruction and training for

Shell Omala S2 G 460

Version 1.1	Revision Date 2024.07.03	Print Date 2024.11.04
	operators.	
Other information	: A vertical bar () in the left margin indicates an amendment from the previous version.	
Sources of key data used to compile the Safety Data Sheet	: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

JP / EN