# Shell Morlina S2 BA 150

Version 1.0		Revision Date 2024.07.29	Print Date 2024.11.05		
1. PRODUCT AND COMPANY IDENTIFICATION					
Chemical product name	:	Shell Morlina S2 BA 150			
Product code	:	001M2919			
Manufacturer or supplier's d Supplier's company name, address and phone number	leta :				
Telephone Telefax	:	(+81) 03-3218-1780 (+81) 03-3218-1781			
Emergency telephone number	:	[Important notice for customer support If you need support for product, please service centre. Lub Customer Service Centre (Lub CS Tel. 0120-064-315 / Fax. 0120-264-31 E-mail. Inquiries-Lubes-JP@shell.com (Available for Japanese office hours or	contact our customer C) 5 (JP Toll free)		
Contact for Safety Data Sheet	:	If you have any enquiries about the c please email lubricantSDS@shell.con			
Recommended use of the chemical and restrictions on use					
Recommended use	:	Machine oil.			
Restrictions on use	:	This substance may not be used for an recommended without expert advice	y purpose other than		

### 2. HAZARDS IDENTIFICATION

#### **GHS** classification of chemical product

Skin sensitisation	: Category 1
Short-term (acute) aquatic	: Category 3
hazard	
Long-term (chronic) aquatic	: Category 3
hazard	

#### **GHS** label elements

# Shell Morlina S2 BA 150

sion 1.0 Hazard pictograms	Revision Date 2024.07.29	Print Date 2024.11
nazaru piciograms		
Signal word	: Warning	
Hazard statements	<ul> <li>PHYSICAL HAZARDS: Not classified as a physical haza HEALTH HAZARDS: H317 May cause an allergic skin ENVIRONMENTAL HAZARDS: H412 Harmful to aquatic life with</li> </ul>	reaction.
Precautionary statements	: <b>Prevention:</b> P273 Avoid release to the enviro P280 Wear protective gloves/ pro protection/ face protection.	
	<b>Response:</b> P302 + P352 IF ON SKIN: Wash P333 + P313 If skin irritation or r advice/ attention.	
	<b>Storage:</b> No precautionary phrases.	
	<b>Disposal:</b> P501 Dispose of contents/ conta disposal plant.	iner to an approved waste
	Additional Information: P261 Avoid breathing dust/ fume P272 Contaminated work clothin the workplace. P321 Specific treatment (see sup on this label). P362 + P364 Take off contamina reuse.	ng should not be allowed o

Contains (4-nonylphenoxy)acetic acid.

#### Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Version 1.0		Revision Date 2024.07.29	Print Date 2024.11.05
Substance / Mixture	:	Mixture	
Chemical nature	:	Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).	

#### Hazardous components

Substance name	CAS-No.	Classification	Concentration (% w/w)
Butylated hydroxytoluene	128-37-0	Aquatic Chronic1; H410 Aquatic Acute1; H400	0.25 - 0.9
(4- nonylphenoxy)acetic acid	3115-49-9	Acute Tox.4; H302 Skin Corr.1B; H314 Skin Sens.1A; H317 Aquatic Acute1; H400 Aquatic Chronic1; H410	0.1 - 0.24
N-phenyl-1- naphthylamine	90-30-2	Acute Tox.4; H302 Skin Sens.1B; H317 STOT RE2; H373 Aquatic Acute1; H400 Aquatic Chronic1; H410	0.1 - 0.24

For explanation of abbreviations see section 16.

IRST-AID MEASURES	
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	: Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
In case of eye contact	: Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue

Version 1.0	Revision Date 2024.07.29 Print Date 2024.11.05
	rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	<ul> <li>Skin sensitisation (allergic skin reaction) signs and symptoms may include itching and/or a rash.</li> <li>Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.</li> <li>Ingestion may result in nausea, vomiting and/or diarrhoea.</li> </ul>
Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Notes to physician	: Treat symptomatically.
5. FIRE-FIGHTING MEASURES	
Suitable extinguishing media	: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	: Do not use water in a jet.
Specific hazards during firefighting	<ul> <li>Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.</li> </ul>
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	: Avoid contact with skin and eyes.
protective equipment and	
emergency procedures Environmental precautions	: Local authorities should be advised if significant spillages
21111 official productions	

Version 1.0	Revision Date 2024.07.29 cannot be contained.	Print Date 2024.11.05
Methods and materials for containment and cleaning up	: Slippery when spilt. Avoid accidents Prevent from spreading by making a or other containment material. Reclaim liquid directly or in an absor Soak up residue with an absorbent s suitable material and dispose of prop	barrier with sand, earth bent. such as clay, sand or other
Additional advice	: For guidance on selection of person see Section 8 of this Safety Data Sh For guidance on disposal of spilled r this Safety Data Sheet.	eet.

7. HANDLING AND STORAGE	
Handling	
Technical measures	<ul> <li>Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.</li> <li>Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.</li> </ul>
Advice on safe handling	<ul> <li>Avoid prolonged or repeated contact with skin.</li> <li>Avoid inhaling vapour and/or mists.</li> <li>When handling product in drums, safety footwear should be worn and proper handling equipment should be used.</li> <li>Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.</li> </ul>
Facial protective equipment	: Wear full face shield if splashes are likely to occur.
Describe contact avoidance, etc	: Strong oxidising agents.
Product Transfer	: Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Storage	
Other data	<ul> <li>Keep container tightly closed and in a cool, well-ventilated place.</li> <li>Use properly labeled and closable containers.</li> </ul>
	Store at ambient temperature.
Packaging material	: Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	: Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

### Shell Morlina S2 BA 150

Version 1.0

Revision Date 2024.07.29

Print Date 2024.11.05

#### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

# Threshold limit value and permissible exposure limits for each component in the work environment

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned			JP OEL JSOH
	Further informa	ation: Group 1: c	arcinogenic to huma	ns
Oil mist, mineral	Not Assigned	OEL-M (Mist)	3 mg/m3	JP OEL JSOH
			e whose OEL is set ba e III, Group 1: carcin	
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

#### **Biological occupational exposure limits**

No biological limit allocated.

#### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

労働者の健康障害を防止するため化学物質の濃度基準値とその適用方法などを定めました (mhlw.go.jp)

<ul> <li>vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.</li> <li>Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.</li> <li>General Information: Define procedures for safe handling and maintenance of controls.</li> <li>Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.</li> <li>Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.</li> <li>Drain down system prior to equipment break-in or maintenance.</li> <li>Retain drain downs in sealed storage pending disposal or</li> </ul>	rsion 1.0	Revision Date 2024.07.29	Print Date 2024.11.05
Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.	Engineering measures	<ul> <li>The level of protection and types of vary depending upon potential exp controls based on a risk assessme Appropriate measures include: Adequate ventilation to control airth Where material is heated, sprayed greater potential for airborne conce General Information: Define procedures for safe handlin controls.</li> <li>Educate and train workers in the h measures relevant to normal activity product.</li> <li>Ensure appropriate selection, testi equipment used to control exposure equipment, local exhaust ventilation Drain down system prior to equipm maintenance.</li> <li>Retain drain downs in sealed storation subsequent recycle.</li> <li>Always observe good personal hyst washing hands after handling the in drinking, and/or smoking. Routine protective equipment to remove comparison.</li> </ul>	of controls necessary will posure conditions. Select ent of local circumstances. porne concentrations. If or mist formed, there is entrations to be generated. Ing and maintenance of mazards and control ities associated with this ing and maintenance of re, e.g. personal protective on. nent break-in or age pending disposal or giene measures, such as material and before eating, by wash work clothing and ontaminants. Discard
		pment	
Personal protective equipment Protective measures		nent (PPE) should meet recommended na	tional standards. Check with
Protective measures Personal protective equipment (PPE) should meet recommended national standards. Check with	Respiratory protection	conditions of use. In accordance with good industrial	hygiene practices,
Protective measures         Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.         Respiratory protection       : No respiratory protection is ordinarily required under normal	Hand protection Remarks	: Where hand contact with the product gloves approved to relevant stands US: F739) made from the following suitable chemical protection. PVC, gloves Suitability and durability of usage, e.g. frequency and duration registering doute	ards (e.g. Europe: EN374, g materials may provide , neoprene or nitrile rubber a glove is dependent on n of contact, chemical

Version 1.0	Revision Date 2024.07.29Print Date 2024.11.05
	gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
	For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.
Eye and face protection	: Wear full face shield if splashes are likely to occur.
Skin and body protection	: Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.
Thermal hazards	: Not applicable
Environmental exposure c	ontrols
General advice	<ul> <li>Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.</li> </ul>
9. PHYSICAL AND CHEMICAL F	PROPERTIES
Physical state	: liquid
Colour	: amber
Odour	: Slight hydrocarbon
Odour Threshold	: Data not available
рH	: Not applicable
pour point	: Method: Unspecified

Melting / freezing pointData not availablepour point-12 °C / 10 °FMethod: ISO 3016

Not applicable

sion 1.0	Revision Date 2024.07.29 : Data not available	Print Date 2024.11.05
Boiling point		
Flash point	: 258 °C / 496 °F Method: ASTM D92 (COC)	
Evaporation rate	: Data not available	
Flammability		
Flammability (solid, gas)	: Not applicable	
Flammability (liquids)	: Not classified as flammable but	will burn.
Lower explosion limit and upp	er explosion limit / flammability limit	
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	: >5	
Density and / or relative dens	ity	
Density	: 887 kg/m3 (15.0 °C / 59.0 °F) Method: DIN EN ISO 12185	
	0.887 kg/m3 (15.0 °C / 59.0 °F) Method: ISO 12185	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: log Pow: > 6 (based on information on simila	r products)
Auto-ignition point	: > 320 °C / 608 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity (Dynamic)	: Data not available	
Viscosity, kinematic	: 135 - 165 mm2/s (40.0 °C / 104 Method: ASTM D445	.0 °F)
	14.7 mm2/s (100 °C / 212 °F) Method: ASTM D445	

Version 1.0		Revision Date 2024.07.29	Print Date 2024.11.0
		150 mm2/s (40.0 °C / 104.0 °F) Method: ASTM D445	
Particle characteristics Particle size	:	Data not available	
Explosive properties	:	Classification Code: Not classified.	
Oxidizing properties	:	Data not available	
Conductivity	:	This material is not expected to be a	a static accumulator.
0. STABILITY AND REACTIVITY			
Reactivity	:	The product does not pose any furth addition to those listed in the followi	
Chemical stability	:	: Stable.	
Possibility of hazardous reactions Conditions to avoid		Reacts with strong oxidising agents	
		Extremes of temperature and direct	sumgnt.
Incompatible materials Hazardous decomposition products	<ul><li>Strong oxidising agents.</li><li>No decomposition if stored and applied as directed.</li></ul>		lied as directed.
1. TOXICOLOGICAL INFORMATI	0	4	
Basis for assessment		Information given is based on data of the toxicology of similar products.Ur the data presented is representative whole, rather than for individual com	nless indicated otherwise, e of the product as a
Information on likely routes of exposure	:	Skin and eye contact are the primar although exposure may occur follow	
cute toxicity			
Product:			
Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classif	inction criteria are not ma

### Shell Morlina S2 BA 150

Version 1.0	Revision Date 2024.07.29	Print Date 2024.11.05
Acute inhalation toxicity	: Remarks: Based on available data are not met.	, the classification criteria
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the class	ification criteria are not met.

#### Skin corrosion/irritation

#### Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

#### Serious eye damage/eye irritation

#### Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitisation

#### Product:

Remarks: Expected to be a skin sensitizer.

#### **Components:**

#### (4-nonylphenoxy)acetic acid:

Remarks: May cause an allergic skin reaction in sensitive individuals.

#### N-phenyl-1-naphthylamine:

Remarks: May cause an allergic skin reaction in sensitive individuals.

#### Germ cell mutagenicity

#### Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

#### Carcinogenicity

#### Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

### Shell Morlina S2 BA 150

Ver	sion 1.0	Revision Date 2024.07.29	Print Date 2024.11.0	5
	Material	GHS/CLP Carcinogenicity Classification	l	
	Highly refined mineral oil	No carcinogenicity classification.		

#### **Reproductive toxicity**

#### Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

#### STOT - single exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

2

#### STOT - repeated exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

#### Aspiration toxicity

#### Product:

Not an aspiration hazard.

#### **Further information**

#### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

#### 12. ECOLOGICAL INFORMATION

Basis for assessment	<ul> <li>Ecotoxicological data have not been determined specifically for this product.</li> <li>Information given is based on a knowledge of the components and the ecotoxicology of similar products.</li> <li>Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).</li> </ul>
----------------------	---

/ersion 1.0		Revision Date 2024.07.29	Print Date 2024.11.05
cotoxicity			
Product:			
Toxicity to fish (Acute toxicity)	:	Remarks: LL/EL/IL50 10-100 mg/l Harmful	I
Toxicity to crustacean (Acute toxicity)	:	Remarks: LL/EL/IL50 10-100 mg/l Harmful	
Toxicity to algae/aquatic plants (Acute toxicity)	:	Remarks: LL/EL/IL50 10-100 mg/l Harmful	
Toxicity to fish (Chronic toxicity)	:	Remarks: Data not available	
Toxicity to crustacean	:	Remarks: Data not available	
(Chronic toxicity) Toxicity to microorganisms (Acute toxicity)	:	Remarks: Data not available	
<u>Components:</u> Butylated hydroxytoluene :			
Toxicity to fish (Acute toxicity)	:	LL50 (Oryzias latipes (Orange-red Exposure time: 96 h Method: Regulation (EC) No. 440/	
Toxicity to crustacean (Acute toxicity)	:	EC50 (Daphnia magna (Water flea Exposure time: 48 h Method: Test(s) equivalent or sim	
M-Factor (Short-term (acute)	:	1	
aquatic hazard) Toxicity to fish (Chronic toxicity)	:	NOEC: 0.53 mg/l Exposure time: 30 d Species: Oryzias latipes (Orange- Method: Test(s) equivalent or sim	
Toxicity to crustacean(Chronic toxicity)	:	NOEC: 0.069 mg/l Exposure time: 21 d Species: Daphnia magna (Water f Method: Test(s) equivalent or sim	
M-Factor (Long-term (chronic) aquatic hazard) <b>(4-nonylphenoxy)acetic acid</b>		1	
M-Factor (Short-term (acute) aquatic hazard) <b>N-phenyl-1-naphthylamine :</b>	:	1	
M-Factor (Short-term (acute) aquatic hazard)	:	1	

# Shell Morlina S2 BA 150

Version 1.0	Revision Date 2024.07.29	Print Date 2024.11.05
M-Factor (Long-term (chronic) aquatic hazard)	: 1	
Persistence and degradability		
Product:		
Biodegradability	: Remarks: Not readily biodegradable., Major constituents are inherently biodegradable, but contains components that may persist in the environment.	
<u>Components:</u> Butylated hydroxytoluene :		
Biodegradability	: Exposure time: 62 d Method: OECD Test Guideline Remarks: Degradation half life 5.65 days	
Bioaccumulation		
Product:		
Bioaccumulation	: Remarks: Contains components with the potential to bioaccumulate.	
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: (based on information on similar products)	
Mobility in soil		
Product:		
Mobility	: Remarks: Liquid under most er enters soil, it will adsorb to soil mobile. Remarks: Floats on water.	
Other adverse effects		
no data available Product:		
Additional ecological information	<ul> <li>Does not have ozone depletior ozone creation potential or glol is a mixture of non-volatile com released to air in any significan conditions of use.</li> <li>Poorly soluble mixture., Cause organisms.</li> <li>Mineral oil does not cause chro organisms at concentrations le</li> </ul>	bal warming potential., Product nponents, which will not be nt quantities under normal es physical fouling of aquatic onic toxicity to aquatic
Hazardous to the ozone layer		
Not applicable		

### 13. DISPOSAL CONSIDERATIONS

#### **Disposal methods**

Version 1.0		Revision Date 2024.07.29	Print Date 2024.11.05
Chemicals (residual waste)	:	<ul> <li>Recover or recycle if possible.</li> <li>It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.</li> <li>Do not dispose into the environment, in drains or in water courses.</li> </ul>	
		Waste product should not be allowed to ground water, or be disposed of into the Waste, spills or used product is danger Waste arising from a spillage or tank cl disposed of in accordance with prevaili preferably to a recognised collector or of competence of the collector or contract established beforehand. Do not dispose of tank water bottoms b drain into the ground. This will result in contamination.	e environment. ous waste. eaning should be ng regulations, contractor. The or should be by allowing them to
		MARPOL - see International Convention Pollution from Ships (MARPOL 73/78) technical aspects at controlling pollution	which provides
Contaminated containers and packaging	:	Dispose in accordance with prevailing it to a recognized collector or contractor. the collector or contractor should be es Disposal should be in accordance with national, and local laws and regulations	The competence of tablished beforehand. applicable regional,
Local legislation Remarks	:	Disposal should be in accordance with national, and local laws and regulations	

### **14. TRANSPORT INFORMATION**

#### Regulatory information when there are domestic regulations

Refer to section 15 for specific national regulation.

#### **International Regulations**

ADR Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Version 1.0	Revision Date 2024.07.29	Print Date 2024.11.05
Special precautions for user		
Remarks	: Special Precautions: Refer to Section 7, Handling & Stora for special precautions which a user needs to be aware of needs to comply with in connection with transport.	

#### **15. REGULATORY INFORMATION**

#### **Related Regulations**

#### **Fire Service Law**

Not dangerous good Designated Flam. Subs, Flammable liquid, (2 cubic metre)

#### **Chemical Substance Control Law**

Priority Assessment Chemical Substance

Chemical name	Number
2,6-Di-tert-butyl-4-methylphenol	64

#### Industrial Safety and Health Law

#### Harmful Substances Prohibited from Manufacture

Not applicable

#### Harmful Substances Required Permission for Manufacture

Not applicable

#### **Substances Prevented From Impairment of Health**

Not applicable

# Circular concerning Information on Chemicals having Mutagenicity - Annex 2: Information on Existing Chemicals having Mutagenicity

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 1: Information on Notified Substances having Mutagenicity

Not applicable

#### Substances Subject to be Notified Names

#### Article 57-2 (Enforcement Order Table 9)

Chemical name	Number	Concentration (%)
Mineral oil	168	>=90 - <=100
2,6-Di-tert-butyl-4-cresol	262	>=0.1 - <1
N-1-naphthylaniline	R04-082	>=0.1 - <1

#### Substances Subject to be Indicated Names

Article 57 (Enforcement Order Article 18)

Chemical name	Number
Mineral oil	168

### Ordinance on Prevention of Hazards Due to Specified Chemical Substances

Not applicable

### Ordinance on Prevention of Organic Solvent Poisoning

Not applicable

# Shell Morlina S2 BA 150

sion 1.0	Revision Date 2024.07.29	Print Date 2024.11.05
Enforcement Orde Substances)	r of the Industrial Safety and Health Law - Atta	ached table 1 (Dangerous
Not applicable		
Poisonous and De	leterious Substances Control Law	
Not applicable		
	on, etc. of Release Amounts of Specific Chem Promotion of Improvements to the Manageme	
Vessel Safety Law		
Not applicable		
Aviation Law		
Not applicable		
Marine Pollution a	nd Sea Disaster Prevention etc Law	
Not classified as ma	arine pollutant	
Water Pollution Co	ontrol Law	
Oil emissions regula	ations (Law Art. 2-5, Enforcement Order Art. 3-4)	
Waste Disposal an	d Public Cleansing Law	
Industrial waste		
The components o	f this product are reported in the following in	ventories:
TSCA	: All components listed.	

: All components listed.

### **16. OTHER INFORMATION**

ENCS

#### Full text of H-Statements

H302	Harmful if swallowed.			
H314	Causes severe skin burns and eye damage.			
H317	May cause an allergic skin reaction.			
H373	May cause damage to organs through prolonged or repeated exposure if swallowed.			
H400	Very toxic to aquatic life.			
H410	Very toxic to aquatic life with long lasting effects.			
Full text of other abbreviations				
Acute Tox.	Acute toxicity			
Aquatic Acute	Short-term (acute) aquatic hazard			
Aquatic Chronic	Long-term (chronic) aquatic hazard			
Skin Corr.	Skin corrosion			
Skin Sens.	Skin sensitisation			
STOT RE	Specific target organ toxicity - repeated exposure			

#### **Abbreviations and Acronyms**

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -

### Shell Morlina S2 BA 150

#### Version 1.0

#### Revision Date 2024.07.29

Print Date 2024.11.05

Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response: ELx - Loading rate associated with x% response: EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet: TCSI - Taiwan Chemical Substance Inventory: TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

#### **Further information**

Training advice	:	Provide adequate information, instruction and training for operators.
Other information	:	A vertical bar ( ) in the left margin indicates an amendment from the previous version.
Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

JP / EN

## Shell Morlina S2 BA 150

Version 1.0

Revision Date 2024.07.29

Print Date 2024.11.05