Version 1.1		Revision Date 2024.07.30	Print Date 2024.11.05
1. PRODUCT AND COMPANY ID	EN.	TIFICATION	
Chemical product name	:	Shell PANOLIN S4 HLP Synth EAL 46	
Product code	:	001M4387	
Manufacturer or supplier's of Supplier's of Supplier's company name, address and phone number	deta :	Shell Lubricants Japan K.K. Pacific Century Place Marunouchi 12F 1-11-1, Marunouchi Chiyoda-ku Tokyo 100-6212	
Telephone Telefax	:	Japan (+81) 03-3218-1780 (+81) 03-3218-1781	
Emergency telephone number	:	[Important notice for customer support] If you need support for product, please service centre. Lub Customer Service Centre (Lub CS Tel. 0120-064-315 / Fax. 0120-264-31 E-mail. Inquiries-Lubes-JP@shell.com (Available for Japanese office hours or	contact our customer C) 5 (JP Toll free)
Contact for Safety Data Sheet	:	If you have any enquiries about the c please email lubricantSDS@shell.com	
Recommended use of the c Recommended use	her	nical and restrictions on use Hydraulic oil	
Recommended use	•		
Restrictions on use	:	This substance may not be used for an recommended without expert advice	y purpose other than

2. HAZARDS IDENTIFICATION

GHS classification of chemical product Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements	
Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	: PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria.

Version 1.1	Revision Date 2024.07.30	Print Date 2024.11.05
	HEALTH HAZARDS: Not classified as a health hazard unde ENVIRONMENTAL HAZARDS: Not classified as an environmental ha:	
Precautionary statements :	Prevention: No precautionary phrases.	
	Response: No precautionary phrases.	
	Storage: No precautionary phrases.	
	Disposal: No precautionary phrases.	

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.High-pressure injection under the skin may cause serious damage including local necrosis.Not classified as flammable but will burn.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	Blend of synthetic esters and additives.

Hazardous components

Contains no hazardous ingredients according to GHS

FIRST-AID MEASURES	
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
	When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the

Shell PANOLIN S4 HLP Synth EAL 46

Version 1.1	Revision Date 2024.07.30 Print Date 2024.11.05
	casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
In case of eye contact	 Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	: Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
	Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.
Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Notes to physician	: Treat symptomatically.
	High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during firefighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs.

Version 1.1	Revision Date 2024.07.30 Unidentified organic and inorga	Print Date 2024.11.05 nic compounds.
Specific extinguishing methods	: Use extinguishing measures the circumstances and the surround	
Special protective equipment for firefighters	: Proper protective equipment in gloves are to be worn; chemica large contact with spilled produ Breathing Apparatus must be w a confined space. Select fire fig relevant Standards (e.g. Europ	Il resistant suit is indicated if ct is expected. Self-Contained vorn when approaching a fire in ghter's clothing approved to

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Avoid contact with skin and eyes.		
Environmental precautions	:	Use appropriate containment to prevent uncontrolled release. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.		
		Local authorities should be advised if significant spillages cannot be contained.		
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.		
Additional advice	:	For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.		

7. HANDLING AND STORAGE

Handling		
Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin.

Shell PANOLIN S4 HLP Synth EAL 46

Version 1.1		Revision Date 2024.07.30	Print Date 2024.11.05
		Avoid inhaling vapour and/or mists. When handling product in drums, safety worn and proper handling equipment sh Properly dispose of any contaminated ra materials in order to prevent fires.	ould be used.
Facial protective equipment	:	If material is handled such that it could a protective eyewear is recommended.	be splashed into eyes,
Describe contact avoidance, etc	:	Strong oxidising agents.	
Storage			
Other data	:	Keep container tightly closed and in a constant place. Use properly labeled and closable contained	
		Store at ambient temperature.	
Packaging material	:	Suitable material: For containers or consteel or high density polyethylene. Unsuitable material: PVC.	tainer linings, use mild
Container Advice	:	Polyethylene containers should not be a temperatures because of possible risk of	

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Threshold limit value and permissible exposure limits for each component in the work environment

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany

Shell PANOLIN S4 HLP Synth EAL 46

Version 1.1	Revision Date 2024.07.30	Print Date 2024.11.05				
	http://www.dguv.de/inhalt/index.jsp L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil					
労働者の健康障害を防止する	ため化学物質の濃度基準値とその適用方法な	ょどを定めました (mhlw.go.jp)				
Engineering measures	 The level of protection and types of vary depending upon potential exploring based on a risk assessme. Appropriate measures include: Adequate ventilation to control airb. Where material is heated, sprayed greater potential for airborne concerned. General Information: Define procedures for safe handling controls. Educate and train workers in the him measures relevant to normal activities product. Ensure appropriate selection, testifie equipment, local exhaust ventilation Drain down system prior to equipment maintenance. Retain drain downs in sealed storations subsequent recycle. Always observe good personal hyge washing hands after handling the right drinking, and/or smoking. Routine protective equipment to remove contaminated clothing and footweappropriates and to the protective equipment to remove contaminated clothing and footweappropriates and the protective equipment to remove contaminated clothing and footweappropriates and the protective equipment to remove contaminated clothing and footweappropriates and the protective equipment to remove contaminated clothing and footweappropriates and the protective equipment to remove contaminated clothing and footweappropriates and the protective equipment to remove contaminated clothing and footweappropriates and the protective equipment to remove contaminated clothing and footweappropriates and the protective equipment to remove contaminated clothing and footweappropriates and the protective equipment to remove contaminated clothing and footweappropriates and the protective equipment to remove contaminated clothing and footweappropriates and the protective equipment to remove contaminated clothing and footweappropriates and the protective equipment to remove contaminated clothing and footweappropriotes and the protective equipment to remove contaminated clothing and footweappropriotes and the protective equipment to remove contaminated clothing and footweappropriotes and the protective equipment to remo	bosure conditions. Select ent of local circumstances. borne concentrations. I or mist formed, there is entrations to be generated. In a g and maintenance of azards and control ities associated with this ing and maintenance of re, e.g. personal protective on. hent break-in or age pending disposal or giene measures, such as material and before eating, ly wash work clothing and ontaminants. Discard				
	Practice good housekeeping.					

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection	 No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter
	appropriate combination of mask and filter.

Version 1.1	Revision Date 2024.07.30 Print Date 2024.11.05
	Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].
Hand protection Remarks	: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
	For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.
Eye and face protection	: If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
Skin and body protection	 Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.
Thermal hazards	: Not applicable
Environmental exposure co	ontrols
General advice	: Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid

contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant

Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing

before discharge to surface water.

vapour.

9. PHYSICAL AND CHEMICAL PROPERTIES

Version 1.1 Revision Date 2024.07.30 Print Date

Print Date 2024.11.05

э. г	IT SICAL AND CITEMICAL FRO	5	ERTIES
	Physical state	:	liquid
	Colour	:	Clear amber
	Odour	:	Data not available
	Odour Threshold	:	Data not available
	рН	:	Not applicable
	pour point	:	-51 °C / -60 °F Method: ASTM D97
	Melting / freezing point		Data not available
	Boiling point, initial boiling point and boiling range	:	> 280 °C / 536 °Festimated value(s)
	Flash point	:	259 °C / 498 °F Method: ASTM D92 (COC) Not applicable
	Evaporation rate	:	Data not available
	Flammability		
	Flammability (solid, gas)	:	Not applicable
	Flammability (liquids)	:	Not classified as flammable but will burn.
	Lower explosion limit and upper	r e	xplosion limit / flammability limit
	Upper explosion limit	:	Typical 10 %(V)
	Lower explosion limit	:	Typical 1 %(V)
	Vapour pressure	:	< 0.5 Pa (20 °C / 68 °F) estimated value(s)
	Relative vapour density	:	> 5
	Density and / or relative density	,	
	Density		919 kg/m3 (15.0 °C / 59.0 °F) Method: ASTM D4052
	Solubility(ies)		
	Water solubility	:	negligible
	Solubility in other solvents	:	Data not available

Shell PANOLIN S4 HLP Synth EAL 46

rsion 1.1 Partition coefficient: n-	Revision Date 2024.07.30 : log Pow: > 6	Print Date 2024.11.0
octanol/water	(based on information on simil	lar products)
Auto-ignition point	: > 320 °C / 608 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity (Dynamic)	: Data not available	
Viscosity, kinematic	: 46.3 mm2/s (40.0 °C / 104.0 ° Method: ASTM D445	F)
	8.6 mm2/s (100 °C / 212 °F) Method: ASTM D445	
	2076 mm2/s (-20 °C / -4 °F) Method: ASTM D445	
	46.3 mm2/s (40.0 °C / 104.0 ° Method: ASTM D445 Not applicable	F)
Particle characteristics Particle size	: Data not available	
Explosive properties	: Classification Code: Not class	ified
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected t	o be a static accumulator.
STABILITY AND REACTIVITY		
Reactivity	: The product does not pose an addition to those listed in the f	
Chemical stability	: Stable.	
Possibility of hazardous reactions	: Reacts with strong oxidising a	gents.
Conditions to avoid	: Extremes of temperature and	direct sunlight.
Incompatible materials	: Strong oxidising agents.	
Hazardous decomposition	: No decomposition if stored an	d applied as directed.

Version 1.1	Revision Date 2024.07.30	Print Date 2024.11.05
products		
11. TOXICOLOGICAL INFORMAT	ION	
Basis for assessment	: Information given is based on dat the toxicology of similar products. the data presented is representat whole, rather than for individual c	Unless indicated otherwise, ive of the product as a
Information on likely routes of exposure	: Skin and eye contact are the prim although exposure may occur foll	
Acute toxicity		
Product:		
Acute oral toxicity	: LD50 rat: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the class	sification criteria are not met.
Acute inhalation toxicity	: Remarks: Based on available dat are not met.	a, the classification criteria
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the class	sification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Shell PANOLIN S4 HLP Synth EAL 46

 Version 1.1
 Revision Date 2024.07.30
 Print Date 2024.11.05

 :
 Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

2

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Version 1.1Revision Date 2024.07.30Print Date 2024.11.05Remarks: Slightly irritating to respiratory system.

12. ECOLOGICAL INFORMATION	
Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on product data, a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Ecotoxicity	
Product:	
Toxicity to fish (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to crustacean (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to fish (Chronic toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Toxicity to crustacean (Chronic toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Toxicity to microorganisms (Acute toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Persistence and degradability	
Product:	
Biodegradability	: Remarks: Readily biodegradable.
Bioaccumulation	
Product:	
Bioaccumulation	: Remarks: Contains components with the potential to bioaccumulate.

Version 1.1	Revision Date 2024.07.30	Print Date 2024.11.05	
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: (based on information on similar products)		
Mobility in soil			
Product:			
Mobility	 Remarks: Liquid under most environm enters soil, it will adsorb to soil particle mobile. Remarks: Floats on water. 		
Other adverse effects			
no data available <u>Product:</u>			
Additional ecological information	 Does not have ozone depletion potent ozone creation potential or global warn is a mixture of non-volatile component released to air in any significant quant conditions of use. Poorly soluble mixture., Causes physic organisms. 	ming potential., Product s, which will not be ities under normal	

Hazardous to the ozone layer

Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal methods

Chemicals (residual waste)	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
	MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Version 1.1	Revision Date 2024.07.30	Print Date 2024.11.05
Contaminated containers and packaging	: Dispose in accordance with prevail to a recognized collector or contract the collector or contractor should be Disposal should be in accordance of national, and local laws and regulat	tor. The competence of e established beforehand. with applicable regional,
Local legislation Remarks	: Disposal should be in accordance v national, and local laws and regulat	

14. TRANSPORT INFORMATION

Regulatory information when there are domestic regulations

Refer to section 15 for specific national regulation.

International Regulations

ADR

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

15. REGULATORY INFORMATION

Related Regulations

Fire Service Law

Not dangerous good Designated Flam. Subs, Flammable liquid, (2 cubic metre)

Chemical Substance Control Law

Not applicable for Specified Chemical Substance, Monitoring Chemical Substance and Priority Assessment Chemical Substance.

Shell PANOLIN S4 HLP Synth EAL 46

Version 1.1	Revision Date 2024.07.30	Print Date 2024.11.05

Industrial Safety and Health Law

Harmful Substances Prohibited from Manufacture

Not applicable

Harmful Substances Required Permission for Manufacture

Not applicable

Substances Prevented From Impairment of Health

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 2: Information on Existing Chemicals having Mutagenicity

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 1: Information on Notified Substances having Mutagenicity

Not applicable

Substances Subject to be Notified Names

Article 57-2 (Enforcement Order Table 9)

Chemical name	Number	Concentration (%)
triethyl phosphate	R05-040	>=0.1 - <1

Substances Subject to be Indicated Names

Not applicable

Ordinance on Prevention of Hazards Due to Specified Chemical Substances

Not applicable

Ordinance on Prevention of Organic Solvent Poisoning

Not applicable

Enforcement Order of the Industrial Safety and Health Law - Attached table 1 (Dangerous Substances)

Not applicable

Poisonous and Deleterious Substances Control Law

Not applicable

Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof

Not applicable

Vessel Safety Law

Not applicable

Aviation Law

Not applicable

Marine Pollution and Sea Disaster Prevention etc Law

Not classified as marine pollutant

Water Pollution Control Law

Oil emissions regulations (Law Art. 2-5, Enforcement Order Art. 3-4)

Version 1.1	Revision Date 2024.07.30	Print Date 2024.11.05	
Waste Disposal and Public Clea	ansing Law		
Industrial waste			
The components of this product are reported in the following inventories:			
TSCA :	All components listed.		
ENCS :	All components listed.		

16. OTHER INFORMATION

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship: REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals: SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet: TCSI - Taiwan Chemical Substance Inventory: TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Further information

Training advice	:	Provide adequate information, instruction and training for operators.
Other information		A vertical bar () in the left margin indicates an amendment from the previous version.

Shell PANOLIN S4 HLP Synth EAL 46

Version 1.1	Revision Date 2024.07.30	Print Date 2024.11.05
Sources of key data used to	. The quoted data are from but not	limited to one or more

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

JP / EN